

Brocade MLX 2-Port 100 GbE CFP2 Module



HIGHLIGHTS

- Maximizes performance and investment protection for new software capabilities at scale with a programmable architecture built on Brocade VersaScale Packet Processor technology
- Delivers 400 Gbps of throughput per half-slot module with full Layer 2, IPv4, IPv6, Multi-Protocol Label Switching (MPLS), and OpenFlow performance
- Provides unmatched scalability with 64 wire-speed 100 GbE ports in a single chassis and support for up to 2 million IPv4 routes and 1 million IPv6 routes
- Aggregates up to 64 100 GbE links in a LAG while supporting up to 6.4 Tbps of capacity in a single trunk
- Delivers integrated support for OpenFlow 1.3 in the industry's only hybrid port mode, enabling Software-Defined Networking (SDN) for increased agility and programmatic control of the network
- Provides a scalable and cost-effective solution for next-generation service provider networks, virtualized data centers, High-Performance Computing (HPC) networks, and large distributed enterprises

High-Performance Terabit Networking Built on Programmable Architecture

Networks today are straining to support unprecedented levels of traffic due to high-bandwidth demands for on-demand personalized content. Leading-edge services such as high-definition video streaming, mobile broadband, and cloud services have significantly altered network traffic behavior. Instead of localized flows with occasional bursts, traffic flows are more collaborative over geographical distances and last longer. These new traffic patterns not only consume enormous amounts of network capacity, but also add a greater degree of complexity to network operations. Additionally, as many organizations look to offer IT services via the cloud, the need for networks to be cloud-optimized and cloud-ready is pressing. As a result, today's network planners are seeking solutions that provide the right mix of scalability, performance, and operational simplicity. High-density 100 Gigabit Ethernet (GbE) can meet rising commodity traffic demands while helping organizations maximize revenue and reduce costs.

Brocade delivers 100 GbE on its flagship routing platform, the Brocade® MLX® Series. The Brocade MLX 2-port 100 GbE CFP2 module provides industry-leading performance and scalability, enabling networks under extreme pressure—such as next-generation service provider networks, virtualized data centers, High-Performance Computing (HPC) networks, and large distributed enterprises—to support increasing application traffic. Each 100 GbE module delivers 400 Gbps of throughput per half-slot module without compromising the performance of features such as Layer 2, IPv4, IPv6, and Multi-Protocol Label Switching (MPLS). This high-capacity module uses less

infrastructure to deliver services to these networks, vastly improving operational efficiency and helping to reduce costs. In addition, the Brocade MLX 2-port 100 GbE CFP2 module comes in two versions, offering a flexible scale-as-you-grow model with hardware Forwarding Information Base (FIB) capacity options in an -M version for up to 512,000 IPv4 routes and 240,000 IPv6 routes, or an -X2 version for up to 2 million IPv4 routes and 1 million IPv6 routes.

Brocade Versascale Packet Processor

The Brocade MLX Series is built on the Brocade VersaScale-200 Packet Processor. The processor is designed

to enable service innovation through programmability and flexibility without sacrificing performance. The Brocade VersaScale-200 provides leading density, zero-packet loss, and line speed for all packet sizes—supporting up to 16,000 simultaneous hardware-multicast entries at line rate.

The Brocade VersaScale-200 is designed for service provider and large-enterprise networks (service-driven IT), and delivers a balance of scalability and feature richness. The processor provides extremely deep packet buffering to handle the dynamic traffic. In addition, it supports large-scale Equal-Cost Multi-Pathing (ECMP) for 32 IPv4 or IPv6 paths, which is ideal for cloud service providers and Web 2.0 companies that need scalable solutions to handle explosive bandwidth growth and to optimize the core for efficient packet transport.

The Brocade VersaScale-200 has distributed network processing and advanced Quality of Service (QoS) capabilities, helping providers tighten their Service Level Agreements (SLAs) for traditional and value-add cloud services. As customers begin to demand network virtualization through Software-Defined Networking (SDN), the ability to easily add new services becomes vital. The Brocade VersaScale-200 is SDN-enabled with OpenFlow support today, and field upgradable for future versions of OpenFlow and other overlay technologies.

Brocade Global Services

Brocade Global Services has the expertise to help organizations build scalable, efficient cloud infrastructures. Leveraging 15 years of expertise in storage, networking, and virtualization, Brocade Global Services delivers world-class professional services, technical

support, and education services, enabling organizations to maximize their Brocade investments, accelerate new technology deployments, and optimize the performance of networking infrastructures.

Affordable Acquisition Options

Brocade Capital Solutions helps organizations easily address their IT requirements by offering flexible network acquisition and support alternatives. Organizations can select from purchase, lease, Brocade Network Subscription, and Brocade Subscription Plus options to align network acquisition with their unique capital requirements and risk profiles. To learn more, visit www.Brocade.com/CapitalSolutions.

Maximizing Investments

To help optimize technology investments, Brocade and its partners offer complete solutions that include professional services, technical support, and education. For more information, contact a Brocade sales partner or visit www.brocade.com.

100 GbE Port Density on Brocade MLX Series Routers

Brocade MLXe Chassis	Wire-Speed 100 GbE Ports
Brocade MLXe-4	8
Brocade MLXe-8	16
Brocade MLXe-16	32
Brocade MLXe-32	64

Brocade MLX 2-Port 100 GbE CFP2 Module Specifications

Item	Maximum Scalability per -M Module	Maximum Scalability per -X2 Module
MAC entries	576,000	1,216,000
IPv4 routes	512,000	2,000,000
IPv6 routes	240,000	1,000,000
Bandwidth per slot	200 Gbps	200 Gbps
Virtual Output Queues (VOQ)	32,000	32,000
Multicast groups	16,000	16,000
Switch fabric modes	Normal and turbo	Normal and turbo
OpenFlow flows	56,000	112,000

Software Feature Highlights

Comprehensive IPv4/IPv6 and Layer 2 support:

- High-performance, robust routing using Forwarding Information Base (FIB) programming in hardware
- RIP/RIPng, OSPF/OSPFv3, IS-IS/IS-IS for IPv6, and BGP-4/BGP-MP for IPv6
- Secure Multi-VRF routing for supporting virtual routing applications over non-MPLS backbones
- VRRP and VRRP-E
- Connecting IPv6 islands over IPv4 MPLS using IPv6 Provider Edge (6PE) routers
- 6VPE enabling IPv6 multitenancy to the edge of the cloud
- BFD Holdover for OSPFv2/3 and IS-IS
- BFD for Static Routes
- BFD for OSPFv3
- ND6 IPv6 Prefix Suppress
- IS-IS Graceful Restart Helper Mode
- 127-Bit IPv6 Interface Addresses

Software-Defined Networking (SDN):

- OpenFlow 1.3: QoS (for metering and enqueue), Group Table (select and fast failover), QinQ (TAG type auto-recognition), Active-Standby Controller, IPv6, Transport Layer Security (TLS) 1.2 (controller interface)
- Brocade OpenFlow in hybrid port mode with support for sFlow-RT, IP, and MPLS/VPLS (uplinks) with protected VLAN for additional flexibility
- Up to 112,000 flows supported
- 12-tuple matching for a diverse set of applications

MPLS support:

- IPoMPLS
- MPLS VPNs: L3 VPNs, L2 VPNs (VPLS, VLL)
- BGP auto-discovery for VPLS endpoints
- MPLS-PBB- (B-VID + I-SID) based interworking
- MPLS over GRE

- BFD for RSVP-TE LSPs
- LDP Inbound and Outbound FEC Filtering
- RSVP Liberal Bypass LSP Selection
- Link Protection Request for RSVP Fast Reroute
- RSVP Hello Messages for Neighbor Failure Detection
- RSVP TE Link Metric for CSPF Computation
- Static Route over RSVP LSP
- Inter-VRF routing with MPLS LSP and MPLS VPN
- Multi-Chassis Trunking (MCT) support for routing over VPLS
- Map a VLL to a specific group of LSPs

Phenomenal scale:

- Carrier trunks: Advanced LAG, ECMP, LSP load balancing
- Terabit trunks with 64x100 GbE LAG

Comprehensive OAM support:

- 802.1ag, Y.1731, 802.3ah, UDLD
- BFD for BGP, OSPF, IS-IS, RSVP LSPs
- Fine-grained timers (3.3 ms) with 802.1ag

Advanced resiliency:

- NSR for OSPF, IS-IS, multicast
- Graceful Restart for BGP, OSPF
- In-Service Software Upgrades (ISSU)

Scalable Carrier Ethernet:

- MEF 9, MEF 14 compliant
- G.8032 v1/v2 for ring resiliency
- MRP (Metro Ring Protocol)
- Virtual Switch Redundancy (VSRP)
- MCT
- Provider Backbone Bridging (PBB)

Advanced visibility, statistics:

- sFlow for granular network traffic accounting
- sFlow support for MPLS LSR and LER interfaces
- Flow- and port-based mirroring
- Per-queue counters
- Per-VLAN, port+VLAN, per-VE counters
- GTP session-based filtering and load balancing

Queuing:

- Virtual Output Queuing (VOQ) architecture
- Up to 2 GB of VOQ buffering per 100 GbE port

Hardware Components :

- Free-scale new generation CPU
- 4 GB DDR3 SDRAM
- 512 KB flash memory boot code
- 64 MB flash memory for application code
- PCIe switch
- 100 Gbps traffic manager
- Network, fabric, stats, CPU interfaces
- DDR3 SDRAM packet buffer
- SP100-XPP FPGA packet processor
- 80 Mb TCAM
- RLDRAM3 LBLRAM
- RLDRAM3 CAM2PRAM
- RLDRAM3 PRAM
- Interlaken system and statistics interfaces
- PBIFS FPGA
- Temperature sensors
- JTAG support
- Hot-pluggable
- Maximum power consumption: 360 W
- Interoperable with 100 GbE CFP optics

Product Support for Optics with Key Standards and Features

Optic Type	IEEE Standards	Electrical Signaling	Fiber Type	Maximum Cable Distance	Digital Optical Monitoring
100GBASE-CFP2-LR4	802.3ba	4x25	SMF	10 km	Yes
100GBASE-CFP2-SR10	802.3ba	10x10	OM3 MMF	100 m	Yes
100GBASE-CFP2-ER4	802.3ba	4x25	SMF	40 km	Yes
100G-QSFP28-SR4	802.3bm	4x25	MMF	70 m (OM3), 100 m (OM4)	Yes
100G-QSFP28-LR4L-2KM	802.3ba	4x25	SMF	2 km	Yes
100G-QSFP28-LR4-10KM	802.3ba	4x25	SMF	10 km	Yes

Brocade MLX 2-Port 100 GbE CFP2 Module Ordering Information

Part Number	Description
BR-MLX-100GX2-CFP2-X2	Brocade MLX 2-port 100 GbE (X2) CFP2 module. Extended route table support for up to 2 million IPv4 and 1 million IPv6 routes in hardware.
BR-MLX-100GX2-CFP2-M	Brocade MLX 2-port 100 GbE (M) CFP2 module. Supports 512,000 IPv4 routes in FIB.

Corporate Headquarters


San Jose, CA USA
T: +1-408-333-8000
info@brocade.com

European Headquarters

Geneva, Switzerland
T: +41-22-799-56-40
emea-info@brocade.com

Asia Pacific Headquarters

Singapore
T: +65-6538-4700
apac-info@brocade.com



© 2015 Brocade Communications Systems, Inc. All Rights Reserved. 09/15 GA-DS-1838-02

ADX, Brocade, Brocade Assurance, the B-wing symbol, DCX, Fabric OS, HyperEdge, ICX, MLX, MyBrocade, OpenScript, The Effortless Network, VCS, VDX, Vplane, and Vyatta are registered trademarks, and Fabric Vision and vADX are trademarks of Brocade Communications Systems, Inc., in the United States and/or in other countries. Other brands, products, or service names mentioned may be trademarks of others.

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment features, or service offered or to be offered by Brocade. Brocade reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This information document describes features that may not be currently available. Contact a Brocade sales office for information on feature and product availability. Export of technical data contained in this document may require an export license from the United States government.

